



By Gun Pro™

## Sight Installation Guide for Glock's

**PLEASE READ AND UNDERSTAND ALL INSTRUCTIONS AND WARNINGS BEFORE USE AND INSTALLATION**

**For 1911 and Smith & Wesson M&P, see Appropriate Installation Guide**

### **WARNING:**

Firearms are classified as dangerous weapons. Injury or death may result from unsafe or improper use. Before installing or adjusting your Delta 1 Sight®, understand and be responsible regarding firearm ownership.

Gun Pro™ strongly advises you to seek the assistance of a reputable gunsmith. Gun Pro™ and its owners or agents will not be held responsible for the result of unauthorized repairs and/or adjustments, or faulty installation. Gun Pro™ and its owners or agents will not be held responsible for careless, unsafe firearm use, or personal injury or property damage of any kind resulting from such use.

It is the responsibility of the user to determine the suitability of the Delta 1 Sight® for any specific use.

- Always treat a firearm as if it were loaded**
- Be sure your firearm is unloaded before making adjustments or installation**
- Never take anyone's word that a firearm is unloaded**
- When a firearm is handed to you, always check that it is unloaded**
- Always keep the muzzle pointed in a safe direction**
- Never point a firearm at an unintended target**
- Never put your hand over the muzzle of a firearm**
- Always keep your firearm unloaded until you intend to shoot**
- Before shooting, make sure of your target and backdrop**
- Always keep your finger(s) off the trigger until aiming at your target and ready to shoot**
- Firearms, alcohol, drugs and certain medications do not mix.**
- Always wear protective eyewear and hearing protection when shooting**

Not all pistols, shooters or ammunition impacts in the same place. Pistols vary, in that even the same model may not shoot to the same point of impact. Ammunition and the individual shooting add an additional variable.

## Note to Gunsmith

### Read **ALL** Instructions **BEFORE** Proceeding

Clean sight dovetail and slide with acetone or alcohol to remove any oil residue.

**IMPORTANT!** Avoid getting alcohol or acetone on the acrylic Delta or any sight adjustment screws which could possibly damage the acrylic Delta or degrade the thread locking compound.

**CAUTION: Acetone is Extremely Flammable!**

Fitting is commonly required as dovetails are most often very tight and slides do vary from gun to gun even of same models. All screws are right hand threads. Make sure the rear dovetail set screws are backed off as to not interfere with installation. Push and drift new rear sight into dovetail. If fitting is required for your Glock, always start by removing material from bottom of male sight dovetail with fine emery stone, or file. Use a black marker to get a visual where there is interference each time you test fit. Stoning is accomplished by applying counted strokes on the stone then rotating the sight base 180 degrees and honing the same amount of strokes to remove material evenly.

Measure sight with calipers often and hand test for fit using a black marker for visual interference. Remove residue from dovetails prior to each test fit.

Once you can readily see the dovetail will fit snugly and completely, use a non-marring punch and drift the sight in place and center on the slide.



**IMPORTANT!** Push or tap only on the base of the dovetail otherwise damage may result.

Once the dovetail on the rear sight is drifted to center, snugly tighten the set screws with the wrench provided while avoiding over tightening.

On the Glock, front sights are installed using a 3/16" hex socket available from many on line retailers. On the rear sight, tighten the two primary set screws snugly.

Your Glock sights have adhesive included and can be applied by user if preferred, however, if new or more thread adhesive is to be applied, remove and clean screws and sight threads with acetone or alcohol to remove any and all oil residue. DO NOT get acetone on the acrylic Delta, damage will result. Then follow instructions provided here:

Knead package well before each use. Apply VC-3 a length of 1 to 1½ times the fastener diameter, filling threads 50-100%. Although material will be dry to touch within minutes, allow VC-3 to dry for 10-30 minutes (the longer the better), depending on part size. Fasteners are then ready for assembly.



**CAUTION** ND VC-3 Adhesive is Flammable, keep from sparks and open flame. Keep screw adhesive away from children. NOT for human consumption. See Material Safety Data Sheet at [www.GunPro.us](http://www.GunPro.us)

## Gun Pro Front Sight Coating

Gun Pro's Front sights come standard with a hard smooth fusion bonded Thermoplastic **Blaze Orange** coating. Front sights are also available with standard uncoated serrations at a minimal cost.

If painting is desired, clean sight area to be painted with acetone or alcohol to remove any oil residue. DO NOT get acetone on the acrylic Delta, damage will result. Avoid getting acetone on any sight adjustment screws which could possibly degrade the thread locking compound.

**CAUTION: Alcohol and Acetone is Flammable!**



*Redefining Performance*

